

ROTARY SNOWBLOWER

225/2, 225/3

225/3



225/2



PRZEDSIĘBIORSTWO PRODUKCYJNO-USŁUGOWO-HANDLOWE

POMAROL S.A.

11-300 Biskupiec ul. Przemysłowa 4

tel. +48 89 715-20-71; fax +48 89 715-20-73, 715-26-78

www.pomarol.com.pl e-mail: sprzedaz@pomarol.com.pl

ROTARY SNOWBLOWER

225-2, 225-3

The Rotary Snowblower is intended for removing snow from the roads, and it is particularly useful for clearing the unhardened roads of snow.

It is suspended on the three point suspension system of an agricultural tractor and it is propelled by a PTO drive shaft from the tractor's power take-off shaft. It is characterised by a simple design.

It is provided with two launchers, which after changing the positions of flaps may direct the snow stream to the left or right side of the road. In Snowblower 225/3 launcher is controlled hydraulically and snow stream can be turned in any direction.

Lp.	Data type		Rotary snow blower 225/2	Rotary snow blower 225/3
1.	Snow throw type		Mechanical control	Hydraulic control
2.	Co-operates with tractors			at least 30 HP
3.	Working width	mm		2260
4.	Depth of snow cower	mm		to 600
5.	Weight	kg	~ 325	~ 355
6.	Snow throw		two-sided	omnidirectional (360°)
7.	Rotational speed			540 rpm
8.	Hydraulic engine		-	BGM 32 C16
9.	PTO drive shaft			LFMR S.A. Lublin
	- symbol			6T-602-4-BA-602
	- nominal torque			540 Nm
	- nominal passed power			30 kW
	- nominal length			980 mm
	- information about „CE” sign			have „CE” sign
	- end from tractor side (spline)			6
	- end from machine side (spline)			6
	- rotational speed			540 rpm
	- overload clutch			yes
	- request power at PTO			30 kW
10.	Nominal working hydraulic pressure	MPa	-	18
11.	Permissible speed			
	- during work	km/h		6
	- during transport	km/h		15
12.	Number of people handling	szt.		1
13.	Noise level	dB		85-90



PRZEDSIĘBIORSTWO PRODUKCYJNO-USŁUGOWO-HANDLOWE

POMAROL S.A.

11-300 Biskupiec ul. Przemysłowa 4

tel. +48 89 715-20-71; fax +48 89 715-20-73, 715-26-78

www.pomarol.com.pl e-mail: sprzedaz@pomarol.com.pl