

# SAND SPREADER PS150, PS200



PRZEDSIĘBIORSTWO PRODUKCYJNO-USŁUGOWO-HANDLOWE  
**POMAROL S.A.**

11-300 Biskupiec ul. Przemysłowa 4  
tel. +48 89 715-20-71; fax +48 89 715-20-73, 715-26-78  
www.pomarol.com.pl e-mail: sprzedaz@pomarol.com.pl

# SAND SPREADER

## PS150, PS200

Sand Spreader mounted on the rear linkage is designed for surface spreading of sand. Box capacity is 1m<sup>3</sup>, working width 2m and a maximum working speed is 10 km/h. That's allow for comfortable use in almost every household. It's a good choice for municipal companies and residential communities. An important feature is possibility to load directly from a pile of sand. The big advantage is the way to dump the sand - it is not scattered by centrifugal method. There is no danger to passers-by and it does not damage parked vehicles near sidewalk. Discharge width is equal to the width of the machine. Drive speed control valve and the lever regulating withd clearance lets you change discharge intensity.

Manufacturer: PPUH POMAROL S.A. 11-300 Biskupiec	SAND SPREADER	
Sand spreader type	PS150	PS200
Working width [mm]	1330	1830
Transporting width [mm]	1700	2200
Length [mm]	1200	
Height [mm]	1350	
Volume of the box [m <sup>3</sup> ]	0,75	1
Weight [~kg]	470	550
Operating personnel	1 person	
Rotational speed of dispensing shaft	max 250 rpm (*)	
Rotational speed of crushing shaft	max 170 rpm (*)	
Working elements drive	Hydraulic	
Working speed	10 km/h	
Transporting speed	15 km/h	

(\*) For a given rotational speed the tractor should have a hydraulic pump with a minimum flow rate 75 l / min



PRZEDSIĘBIORSTWO PRODUKCYJNO-USŁUGOWO-HANDLOWE

**POMAROL S.A.**

11-300 Biskupiec ul. Przemysłowa 4

tel. +48 89 715-20-71; fax +48 89 715-20-73, 715-26-78

www.pomarol.com.pl e-mail: sprzedaz@pomarol.com.pl